

# PACKING BODY OF SENSOR AND ITS USING METHOD


**Patent number:** JP2000314711  
**Publication date:** 2000-11-14  
**Inventor:** KUSHIMACHI TETSUO  
**Applicant:** GUNZE KK  
**Classification:**  
- international: G01N27/00; B65D77/02; B65D85/38; G01N27/28  
- european:  
**Application number:** JP19990125525 19990506  
**Priority number(s):** JP19990125525 19990506

[Report a data error here](#)

## Abstract of JP2000314711

**PROBLEM TO BE SOLVED:** To provide a packing body whose handling performance is excellent even if a sensor is downsized and whose storage performance is excellent.

**SOLUTION:** This is a packing body 10 which stores and packs a sensor 5 in which a sensor part 2 and a connector part 3 are respectively formed at one end and the other end of a substrate. The packing body 10 is equipped with a packing body main body 16 having a sensor holding part 12 which has a bottom and at least stores and holds the sensor part 2 of the sensor 5 and a connector storing part 14 which has an opening cross section larger than that when connected to a sensor holding part 12 and accommodates a connector part 3, and a cover 18 which can close an opening of the connector storing part 14.



Data supplied from the [esp@cenet](mailto:esp@cenet) database - Worldwide

**Partial Translation of JP 2000-314711**

**Publication Date:** November 14, 2000

**Application No.:** 1999-125525

**Filing Date:** May 6, 1999

**Applicant:** GUNZE KK

**Inventor:** Tetsuo KUSHIMACHI

[Claim 6] The packing body for sensor according to claim 2, wherein  
the cover member is formed of a transparent material or a material on which  
a sensor removal position is printed.